

TRANSMISSION

AUTOMOTIVE LUBRICANTS



ALWAYS MOVING FORWARD.

 **LUKOIL**
LUBRICANTS

TRANSMISSION

LUKOIL TRANSMISSION LS 80W-90	
LUKOIL TRANSMISSION LS 85W-90	
LUKOIL TRANSMISSION B 85W-90	
LUKOIL TRANSMISSION B 80W-90	7
LUKOIL TRANSMISSION B 80W-140	
LUKOIL TRANSMISSION B 85W-140	
LUKOIL TRANSMISSION LD 80W-90	
LUKOIL TRANSMISSION SYNTH BSX 75W-90	8
LUKOIL ATF	
LUKOIL ATF SYNTH M 15	
LUKOIL ATF SYNTH M 14	
LUKOIL ATF SYNTH MN Z3	9
LUKOIL ATF SYNTH MULTI	
LUKOIL ATF SYNTH CVT	
LUKOIL ATF SYNTH VI	10
LUKOIL DCTF	
LUKOIL ATF SYNTH	
LUKOIL TRANSMISSION SYNTH MN Z5 75W-80	
LUKOIL TRANSMISSION SLY 75W-90	
LUKOIL TRANSMISSION SYNTH MPX 75W-80	12
LUKOIL TRANSMISSION SYNTH MPX 75W-90	
LUKOIL TRANSMISSION MP 80W-85	
LUKOIL TRANSMISSION MP 85W-90	
LUKOIL TRANSMISSION MP 75W-80	13
LUKOIL TRANSMISSION LDI 75W-80	
LUKOIL TRANSMISSION UNI S 75W-140	
LUKOIL TRANSMISSION UNI S 75W-90	
LUKOIL TRANSMISSION UNI 80W-90	14

LUKOIL LUBRICANTS ENABLE RELIABLE MOBILITY FOR MILLIONS WORLDWIDE AND PROVE THEMSELVES DAILY UNDER ALL CONDITIONS.

Lubricants are some of the most important technical components of our daily life – and yet they are rarely noticed. And so it should be. After all, safety and progress can only be guaranteed by high-quality products with long service lives that invisibly keep our ever more dynamic world turning smoothly. LUKOIL Lubricants takes its responsibility as a manufacturer of first-class, reliable lubricants extremely seriously. The company's products are used across a range of industries, ensuring the smooth functioning of vehicles as well as boats and agricultural machinery.

In this way, LUKOIL helps keep today's highly complex logistics networks from grinding to a halt – which would be unthinkable in our modern ultramobile society. Nor is coming to a halt an option for the LUKOIL company. Stable growth, securing of resources and steady improvement of products and processes are essential in a highly dynamic market. LUKOIL has therefore established the goal of being at the absolute top in the most challenging segment: fully synthetic, high-performance oils for modern vehicle engines. The development of LUKOIL TRANSMISSION is an impressive and successful example of this strategy – but we are always striving for more.

Founded in 1991 by a merger of regional oil and gas transport companies in the western Siberian cities of Langepas, Uray and Kogalym (LUK), LUKOIL developed into the largest private oil group in Russia. In line with its established creed of vertical integration – in other words raw material extraction, production and development as well as sales of high-quality products all at a single company – LUKOIL always strives to offer perfect service to its customers. In recent years,



the focus here has been on the lubricants business. Through constant development work at seven refineries and production sites in Europe, including the newly added production and filling plant at the oil port of Lobau, LUKOIL Lubricants has already won over more than 300 manufacturers in the automotive industry, especially with the high-quality oils for the critical European market.

The Austrian market is also gaining in importance here. After all, it is from here that LUKOIL serves all Western European countries, not only with production and development, but also with the operation of a highly efficient distribution network. The lion's share of the value creation is therefore situated in Austria – at the heart of Europe. An important signal of stability and a long-term orientation. The decades of experience of Austrian experts in the role of a Central European hub and interface between East and West also ensure smooth functioning of all critical logistical flows. With the Danube port of Lobau and the Vienna Airport, high-capacity transport routes are a given.



LUKOIL TRANSMISSION

THE PREMIUM TRANSMISSION OIL FROM LUKOIL IS PREPARING TO CONQUER THE EUROPEAN MARKET FROM VIENNA – WITH HIGH QUALITY AND A SUSTAINABLE BUSINESS MODEL.

With the expansion of the Vienna production site and the associated strict quality controls, LUKOIL is sending a strong signal for the quality standard of LUKOIL TRANSMISSION. As a home for modern technology enterprises, Austria also guarantees a product that not only meets the strict quality, environmental and ethical standards in Austria but subsequently throughout Europe as well.

LUKOIL TRANSMISSION was specially developed to ensure smooth operation over the entire service period. High-quality base oils and state-of-the-art additive technologies effectively minimise wear, oxidation and friction.

To give your vehicle the best, choose LUKOIL TRANSMISSION.



**QUALITY IS OUR STRENGTH.
TRANSMISSIONS ARE OUR PASSION.**

QUALITY FROM AUSTRIA

In our state-of-the-art production facilities in Lobau, Vienna, as well as in Finland and Romania, we manufacture over 40,000 tonnes of lubricant every year, using first-class source materials. Our scientific experts also work continuously to improve our products to guarantee ever greater reliability and progress.

In this way, LUKOIL can supply customers around the world – even in the most demanding segment of fully synthetic, high-performance lubricants – with reliable and individual solutions for special applications.

IT'S A MATTER OF TRUST.

TRANSMISSION

AUTOMOTIVE LUBRICANTS



LUKOIL TRANSMISSION LS 80W-90

Prod. No.: 582515

APPROVALS

ZF TE-ML 05C/ 12C/ 21C
(ZF003406)

SPECIFICATIONS

API GL-5
ZF TE-ML 16E

- Used for differentials with limited slip and heavily loaded axle transmissions, utility vehicles, tractors and construction machinery

- Universal transmission oil with extremely stable viscosity for heavy loads in axle transmissions as per the manufacturer specifications

- Features state-of-the-art anti-wear additives and a reliably constant coefficient of friction



LUKOIL TRANSMISSION LS 85W-90

Prod. No.: 582520

APPROVALS

ZF TE-ML 05C/ 12C/ 21C
(ZF003494)

SPECIFICATIONS

API GL-5
ZF TE-ML 07A/ 08/ 16E



LUKOIL TRANSMISSION B 85W-90

Prod. No.: 583210

APPROVALS

MB-Approval 235.0
ZF TE-ML 16C/ 17B/ 19B/ 21A
(ZF001762)

SPECIFICATIONS

API GL-5
FENDT
FORD M2C-94A
MIL-L-2105D
NH 520
STEYR G
TATRA TDS 80/32
VOITH 3.325-339
VOITH VSN 6086/19/20
VOLVO 97310
ZF TE-ML 07B/ 08

- The mineral axle transmission oil is used primarily in utility vehicles for standard oil change intervals with maximum load-bearing capacity

- Axle transmission oil with good ageing stability

- Offers optimal wearing and corrosion protection, ensures a long transmission lifespan

- The transmission oil stands up to the hardest loads and is suitable for hypoid transmissions with extreme axial offset in vehicles and machinery



LUKOIL TRANSMISSION B 80W-90

Prod. No.: 583220

SPECIFICATIONS

API GL-5
MAN 342 Typ M1
MB 235.0
MIL-L-2105D
VOITH 3.325-339
VOLVO 97310
ZF TE-ML 07A/ 08/ 16B/ 17B/ 19B/ 21A

LUKOIL TRANSMISSION B 80W-140



Prod. No.: 583221

SPECIFICATIONS

API GL-5
MIL-L-2105D
VOLVO 97310
ZF TE-ML 07A/ 08/ 16D/ 21A

- Mineral transmission oil for axle transmissions
- Exhibits extreme age stability. Offers maximum load capacity and excellent shear stability
- Ensures a long lifespan for the transmission
- Features low viscosity temperature dependence

LUKOIL TRANSMISSION B 85W-140



Prod. No.: 583222

SPECIFICATIONS

API GL-5
MIL-L-2105D
NH 524A
VOLVO 97310
ZF TE-ML 07A/ 08/ 16D/ 21A

LUKOIL TRANSMISSION LD 80W-90



Prod. No.: 583630

APPROVALS

SPECIFICATIONS

- Mineral axle transmission oil used primarily in utility vehicles
- Offers high load capacity and better thermal stability while enabling longer oil change intervals
- Extreme ageing stability for a long lifespan

MAN 342 Typ M3
MAN 341 Typ GA1
MB-Approval 235.20
Scania STO 1:0

API GL-5/ MT-1
MIL-PRF-2105E
SAE J2360
ZF TE-ML 05A/ 07A/ 12L/ 12M/ 16B/ 17B/ 19B/ 21A

LUKOIL TRANSMISSION SYNTH BSX 75W-90



Prod. No.: 583270

APPROVALS

SPECIFICATIONS

- Fully synthetic, fuel-efficient axle transmission oil, primarily suitable for utility vehicles
- Developed for maximum loads, giving the axle transmission oil extreme ageing resistance
- Enables the longest oil change intervals
- Contains state-of-the-art, high-performance anti-wearing additives for a long transmission lifespan

MAN 341 Typ Z2
MAN 342 Typ S1
MB-Approval 235.8
Scania STO 1:0
VOLVO 97312
ZF TE-ML 05A/ 12B/ 16F/ 17B (ZF001763)

API GL-5
MIL-PRF-2105 E
ZF TE-ML 02B/ 07A/ 08/ 12L/ 12N/ 19C/ 21B

TRANSMISSION

AUTOMOTIVE LUBRICANTS



LUKOIL ATF

Prod. No.: 583315	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> The universal, partly synthetic automatic transmission oil was developed for both cars and trucks Excellent viscosity and temperature behaviour Excellent ageing and foaming behaviour, very good flow properties at low temperatures and reliable protection against wear and corrosion Used as a power transmission medium in automatic transmissions of cars, buses and all-terrain vehicles 	MAN 339 L1/V1/Z1 VOITH H55.6335.XX ZF TE-ML 04D/ 14A (ZF001146)	Allison C-4 Caterpillar TO-2 GM DEXRON® II-D/ III-G MAN 339 Typ D/ F MB 236.1 RBAS TE-ML 09 VOLVO 97340/ 97341 ZF TE-ML 11A/ 11B/ 17C



LUKOIL ATF SYNTH M 15

Prod. No.: 583325	APPROVALS
<ul style="list-style-type: none"> High-quality automatic transmission oil for service fillings on Mercedes 7-speed automatic transmissions Characterised by high fuel savings Optimal friction properties mean longer change intervals 	MB-Approval 236.15



LUKOIL ATF SYNTH M 14

Prod. No.: 583326	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> Newly developed, synthetic, red-coloured, automatic transmission fluid, specially for the newest MERCEDES BENZ 7-speed automatic transmission (NAG 2, type 722.9) Also backwards-compatible with all 5-speed automatic transmissions (type 722.6), it has proven itself well in older automatic transmissions to restore declining ease of shifting For maximum ease of shifting 	MB-Approval 236.14	MB 236.10/ 11/ 12 ZF TE-ML 11A/ 11B



LUKOIL ATF SYNTH MN Z3

Prod. No.: 583335	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> High-quality universal automatic transmission fluid developed for utility and passenger vehicles Low viscosity temperature dependence (high viscosity index) and excellent ageing properties Enables the longest oil change intervals Stable glide properties enable soft shifting without vibration 	MAN 339 Typ V2/ Z3/ Z12 VOITH H55.6336.XX ZF TE-ML 04D/ 14C/ 16M/ 16S/ 20C/ 25 (ZF001302)	Allison C-4/ TES-295/ TES-389 Ford MERCON V/ MERCON GM DEXRON® IID/ III-G/ III-H JASO M315 1A MAN 339 Typ L1 MB 236.6 RBAS TE-ML 09 VOLVO 97341 ZF TE-ML 11A/ 11B/ 16L/ 21L

LUKOIL ATF SYNTH MULTI



Prod. No.: 583340

APPROVALS

SPECIFICATIONS

- High-quality universal automatic transmission fluid for passenger and utility vehicles
- Characterised by low viscosity temperature dependence (high viscosity index) and excellent ageing properties

MAN 339 L1/V2/ Z2/ Z11
MB-Approval 236.6/ 236.9
VOITH H55.6336.XX
VOLVO 97341
ZF TE-ML 04D/ 14B/ 16L/
 16R/ 20B/ 25B

Aisin Warner AW-1
Allison C-4/ TES-295/ TES-389
BMW ETL 7045E/ 8072B
Chrysler MS 10838/ 5931/
 7176D (ATF +2)/ MS 7176E (ATF +3)/
 MS 9602 (ATF +4)
Fiat 9.55550-AV1
Ford M2C195-A/ MERCON V/ MERCON
GM 9985010
DEXRON® III-H
Honda ATF-Z1
Hyundai NWS 9638/ PSF-3/ PSF-4
Hyundai/Kia SP-II/ -III/ -IV
JASO M315 1A
JWS 3309/ 3314/ 3324 (ATF WS)
MB 236.10/ 236.11/ 236.3/ 236.91
Nissan Matic D/ J/ K/ S/ PSF-II
Subaru ATF
Suzuki ATF 3317
Toyota Typ T/ T-II/ T-IV
VOLVO 1161540/ 97340
VW G 052 162/ 052 990/ 055 025

LUKOIL ATF SYNTH CVT



Prod. No.: 583345

SPECIFICATIONS

- High-quality automatic transmission fluid for continuously variable passenger car transmissions
- Excellent anti-foaming properties and no negative impact on seal materials
- Improved anti-corrosion properties reliably protect all system components
- Optimal glide properties for wet clutches and belt pulley pairs

Daihatsu CVTF DC/ DFE
Dodge/Jeep CVTF+4/ NS-2
Ford CVT 23/ CVT 30 / MERCON C
GM CVT
Honda HFC-2/ HMMF
Hyundai/Kia SP-III / Genuine CVTF
MB 236.20
MINI ELZ 799
Mitsubishi CVTF-Diaqueen J1/ J4/ SP-III
Nissan NS-2/ NS-3
Punch Powertrain CVTF EX-1/ CVT-PPT/ EZL799A
Subaru CVTF/ NS-2
Suzuki CVT Green 1/ 2 / NS-2/ TC
Toyota TC
VW G 052 180 / 052 516





WHICH TRANSMISSION OIL DO I NEED?

Information on other car brands can be obtained in the LUKOIL Oilfinder at www.lukoil-lubricants.eu or at technics.lubes@eu.lukoil.com



LUKOIL ATF SYNTH VI

Prod. No.: 583346	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> ■ High-quality automatic transmission fluid developed for passenger cars and light utility vehicles ■ Characterised by low viscosity temperature dependence and outstanding protection against sludge formation ■ No negative impact on seal materials ■ Improved anti-corrosion properties reliably protect all system components 	GM DEXRON® VI	Bentley PY112995PA BMW/MINI 83 22 0 142 516/ 83 22 0 163 514/ 83 22 0 397 114/ 83 22 2152 426 Chrysler 05127382AA/ 68043742AA/ 68157995AA Ford XT-10-QLV/ XT-6-DSP/ XT-6-QSP GM 88863400/ 88863401 / AW1 Honda DW-1 Hyundai/Kia NWS-9638 T-5 / P/N 040000C90SG / SPH-IV/ SP-IV Jaguar Fluid 8432 JASO M315 1A Land Rover LR0022460/ TYK500050 Maserati 231603 Mazda FZ MB 236.12/ 236.14/ 236.15/ 236.41 Mitsubishi ATF-J3 Nissan Matic S Porsche 000 043 304 00 Saab 93 165 147-AW-1 Toyota Typ WS VW G 052 533 /055 005 (-A; A2) / G 055 162 (A2/A6) / 055 540 (A2)/ G 060 162 (A1/A2/A6)

PACKAGING INFORMATION

PACKAGING	TARE BOX (KG)	TARE CONTAINER (KG)	WIDTH (MM)	HEIGHT (MM)	LENGTH (MM)	DIA-METER (MM)	UNITS PER PALLET	PALLET SIZE (CM)	UNITS PER SALE UNIT
1 LITRE BOTTLE	0,35	0,08	260	240	380	–	432	120 x 80	12
5 LITRE BOTTLE	0,32	0,3	260	330	380	–	81	120 x 80	3
20 LITRE CANISTER	–	1,0	260	362	300	–	36	120 x 80	–
DRUM 60 LITRES	–	4,0	–	586	–	384	6	120 x 80	–
DRUM 205 LITRES	–	14,5	–	878	–	585	4	120 x 120	–
IBC CONTAINER 1000 LITRES	–	60	1000	1200	1200	–	–	–	–

LUKOIL DCTF



Prod. No.: 583370

SPECIFICATIONS

- Dual clutch transmission oil for diverse applications
- Offers optimal wearing protection and ensures silky smooth shifting

BMW 83 22 0 440 214/ 2 147 477/
2 148 578/ 2 148 579/ DCTF-1/ MTF LT-5
Chrysler
Ford WSS-M2C936-A
MB 236.21/ 236.24/ 236.25
Mitsubishi Dia-Queen SSTF-1/ MZ320065
Nissan WSS-M2C936-A
Porsche Oil No. 999.917.080.00
PSA 9734.S2
VOLVO 1161838/ 1161839
VW G 052 182/ 052 529/ 055 529

LUKOIL ATF SYNTH



Prod. No.: 583321

APPROVALS

SPECIFICATIONS

- Fully synthetic, red-coloured, high-performance transmission fluid
- Characterised by maximum shear stability, outstanding oxidation stability and excellent flow behaviour even at extremely low temperatures
- Precise shifting thanks to optimal foaming behaviour. Reliable wearing and corrosion protection also ensure high driving comfort

MAN 339 Typ L1/ V2/ Z2
MB-Approval 236.8
RABAS Lubricant Class
TE-ML 09X
VOTH H55.6336.xx
ZF TE-ML 04D/ 14B/ 16L

Allison C-4
DIN 51 524-HVLP
Ford MECRON
GM DEXRON® II-E
NATO Code H-548
VOLVO 97335
ZF TE-ML 11A/ 21L

LUKOIL TRANSMISSION SYNTH MN Z5 75W-80



Prod. No.: 582010

SPECIFICATIONS

- Specially developed for use in heavily loaded manual and automatic transmissions operating under the harshest conditions
- Particularly suitable for ZF utility vehicle transmissions with intarder
- Guarantees the longest oil change intervals and reduces fuel consumption

API GL-4
MAN 341 Typ Z5
MB 235.28
VOITH Oil Class C
VOLVO 97307
ZF TE-ML 01E/ 02E/ 16P

LUKOIL TRANSMISSION SLY 75W-90



Prod. No.: 582010

SPECIFICATIONS

- Synthetic transmission oil for passenger cars, offers maximum ease of shifting even at low winter temperatures
- Exhibits extreme ageing and shear stability to ensure long oil change intervals
- Offers optimal wearing and corrosion protection

API GL-4+
VW 501.50

TRANSMISSION

TRANSMISSION OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY



LUKOIL TRANSMISSION SYNTH MPX 75W-80

Prod. No.: 583060

APPROVALS

MAN 341 Typ VR
MB-Approval 235.29
VOITH Oil Class C
VOITH Retarder
VOLVO 97307

SPECIFICATIONS

API GL-4
EATON Transmission
MAN 341 Typ E4

- A fully synthetic, fuel-efficient transmission oil specially formulated for Mercedes Benz utility vehicles for extremely long oil change intervals
- Impresses with extreme ageing stability and long lifespan thanks to modern, high-performance wearing protection additives
- Ensures high shifting quality



LUKOIL TRANSMISSION SYNTH MPX 75W-90

Prod. No.: 583070

SPECIFICATIONS

API GL-4
MAN 341 Typ MB
MB 235.4/ 235.11
ZF TE-ML 08



LUKOIL TRANSMISSION MP 80W-85

Prod. No.: 583010

APPROVALS

MB-Approval 235.1

SPECIFICATIONS

API GL-4
ZF TE-ML 08/ 16A/ 17A/ 19A

- Mineral transmission oil with high pressure absorption capacity, primarily for manual transmissions
- Top manual transmission oil with good ageing stability and very high load-bearing capacity
- Ensures an extremely long transmission lifespan thanks to optimal wearing and corrosion protection additives
- Low pour point, low viscosity temperature dependence



LUKOIL TRANSMISSION MP 85W-90

Prod. No.: 583020

APPROVALS

MB-Approval 235.1
ZF TE-ML 16A/ 17A/ 19A
(ZF003413)

SPECIFICATIONS

API GL-4
MIL-L-2105
ZF TE-ML 08



LUKOIL TRANSMISSION MP 75W-80

Prod. No.: 583021

SPECIFICATIONS

- Synthetic, fuel-efficient transmission oil specially for passenger cars and light utility vehicles with extremely long oil change intervals
- Optimal wearing and corrosion protection
- High ageing stability and long lifespan

API GL-3/ -4/ -4+ (transl. NFI/ NFP/ TRI/ TRT/ TRZ)
BMW MTF LT-2/ LT-3/ LT-4
Fiat 9.5555.0 – MZ1
Ford WSD-M2C200-C/ -D2
GM 1940004/ 19259104 (BOT 303)/ 1940182/ 1940764/ 1940768
MB 235.10/ 235.3
Nissan MT-XZ/ MT-XZ TL (JR Type)
PSA B71 2330
Special Gear Oil MTF 94/ Honda MTF/ -II/ -III
VOLVO 97308/ 97309
VW G 052 171/ 052 178/ 052 512/ 052 527 (A2)/ 052 726 (A2)/ 060 726/ 009 317/ G50



LUKOIL TRANSMISSION LDI 75W-80

Prod. No.: 583620	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> Synthetic, fuel-efficient transmission oil, specially suited for utility vehicles, ensures extremely long oil change intervals Good ageing stability, ensures long transmission lifespan thanks to modern wearing protection additives Optimal wearing and corrosion protection Maximum compressive strength of the lubrication film for optimal lubrication reliability 	MAN 341 Typ Z4 ZF TE-ML 02L/ 16K (ZF001767)	API GL-4 DAF IVECO 18-1807 MGS1 Renault VOITH Oil Class C VOLVO 97305 ZF TE-ML 01L/ 02D/ 07A/ 08



LUKOIL TRANSMISSION UNI S 75W-140

Prod. No.: 583535	SPECIFICATIONS
<ul style="list-style-type: none"> Fully synthetic, high-performance universal transmission oil for synchronised and unsynchronised manual transmissions and axle transmissions High ageing resistance and long service periods are guaranteed Neutral behaviour with respect to non-ferrous metals and elastomers 	API GL-5/ MT-1 SAE J2360 Scania STO 1:0 VOLVO 97310 ZF TE-ML 05A/ 07A/ 08/ 12B/ 16F/ 21A



LUKOIL TRANSMISSION UNI S 75W-90

Prod. No.: 583520	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> Fuel-efficient, fully synthetic, high-performance universal transmission oil for synchronised and unsynchronised manual transmissions and axle transmissions Reduces fuel consumption Characterised by high ageing resistance and long service periods Neutral behaviour with respect to non-ferrous metals and elastomers 	MAN 341 Typ Z2/ S1 ZF TE-ML 02B/ 05B/ 12L/ 12N/ 16F/ 17B/ 19C/ 21B (ZF001769)	API GL-4/ GL-5/ MT-1 MAN 341 Typ E2/ E3 MAN 342 Typ M3 MB 235.0/ 235.8 MIL -PRF-210SE SAE J2360 Scania STO 1:0 VOLVO 97312 ZF TE-ML 07A/ 08/ 12B



LUKOIL TRANSMISSION UNI 80W-90

Prod. No.: 583510	APPROVALS	SPECIFICATIONS
<ul style="list-style-type: none"> High-performance universal transmission oil for manual transmissions and axle transmissions High ageing-resistance and long service periods Protects against wear and optimises the lifespan of the transmission 	MAN 341 Typ Z2 MAN 342 M2 ZF TE-ML 02B/ 05A/ 12L/ 12M/ 16B/ 17H/ 19B/ 21A (ZF001768)	API GL-4/ -5/ MT-1 ARVIN MERITOR 0-76-D MAN 341 Typ E2 MB 235.0 MIL -PRF-210SE SAE J2360 Scania STO 1:0 ZF TE-ML 05B/ 07A/ 08/ 16C/ 19C/ 21B

LUKOIL LUBRICANTS EUROPE GmbH

1220 Vienna, Uferstrasse 8
www.lukoil-lubricants.eu
Version: 1.0, November 2019

MORE INFORMATION AVAILABLE FROM:

AUSTRIA

Automotive: Telephone 0810 959 8884
info.schmierstoffe-automotive@eu.lukoil.com
Industry: Telephone 0810 959 8886
info.schmierstoffe-industry@eu.lukoil.com
Dealer: Telephone 0810 959 8885
info.schmierstoffe-dealer@eu.lukoil.com

GERMANY

Automotive: Telephone 01806 06 00 004
info.schmierstoffe-automotive@eu.lukoil.com
Industry: Telephone 01806 06 00 006
info.schmierstoffe-industry@eu.lukoil.com
Dealer: Telephone 01806 06 00 005
info.schmierstoffe-dealer@eu.lukoil.com

CZECH REPUBLIC

Telephone 844 900 033
info.lubes-CEE@eu.lukoil.com

HUNGARY

Telephone 0680 980 975
info.lubes-CEE@eu.lukoil.com

SLOVAKIA

Telephone 0850 166 670
info.lubes-CEE@eu.lukoil.com

ITALY

Telephone +43 1 205 222 8007
info.lubes-CEE@eu.lukoil.com

SWEDEN

Telephone +46 (0)8 466 88 60
order.se@eu.lukoil.com



LUKOIL
IN MY HEART



WWW.LUKOIL-LUBRICANTS.EU